

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project : | |
|-----------------|------|
| Model #: | |
| Item #: | Qty: |
| Available W/H : | |
| Approval: | |

Model: TCDD-72H-W(B)-N

Direct Cooling Type Cases

Bakery & Deli Cases High Profile

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



* Black and white color come standard

== FEATURES & BENEFITS ==_

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Attractive, elegant, glass sided Euro design

Curved tempered front glass and minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Low-E coated double pane glass is tempered for safety
- Easy access control panel
- Sliding rear doors for product loading & unloading
- Heavy duty, white PE coated wire shelves
- Cantilever wired shelves adjustable up and down, tilted
- Stainless steel floor and airflow grille
- Rear access to compressor compartment for quick and easy service
- Refrigerated deli case holds avg. 33°F ~ 41°F for fresher products











| Model | CU./FT. | # of Shelves | HP | AMPS | Crated Weight (lbs.) | L x D x H (inches) |
|-----------------|---------|-----------------|-----|------|-------------------------|-----------------------|
| TCDD-72H-W(B)-N | 24.7 | 2 | 3/4 | 7.8 | 777 | 721/2 x 30 x 501/8 |

Direct Cooling Type Cases

Model: TCDD-72H-W(B)-N

| ELECTRICAL DATA | | | | |
|---------------------------|----------------------------|--|--|--|
| Voltage | 115/60/1 | | | |
| Plug Type | ① NEMA 5-15P | | | |
| Full Load Amperes | 7.8 | | | |
| Compressor HP | 3/4 | | | |
| Refrigerant | R-290 | | | |
| DIMENSIONAL DATA | | | | |
| Net Capacity (cu. ft.) | 24.7 | | | |
| Ext. Length Overall (in.) | 72 _{1/2} (1842mm) | | | |
| Ext. Depth Overall (in.) | 30 (762mm) | | | |
| Ext. Height Overall (in.) | 50 _{1/8} (1273mm) | | | |
| Int. Length Overall (in.) | 691/4 (1757mm) | | | |
| Int. Depth Overall (in.) | 24 (610mm) | | | |
| Int. Height Overall (in.) | 235/8 (599mm) | | | |
| Shelf Size (in.) | 681/4 x 153/4 | | | |
| Shelf Size (in.) | 681/4 x 173/4 | | | |
| Net Weight (lbs.) | 639 | | | |
| Gross Weight (lbs.) | 777 | | | |
| # of Shelves | 2 | | | |
| Power Cord Length (in.) | 591/8 | | | |

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor


STANDARD FEATURES

- · Anti-corrosion coated evaporator
- · Self-contained system, no plumbing required
- · Safety shielded LED lighting interior
- · Solar powered digital thermometer
- · Digital electronic thermostat with defrost control
- · White and black colors come standard
- Recommended operating conditions:

TCDD models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product.

PLAN VIEW (unit: inch)





Ver 20181210



■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002









